





BLOCK Series - IP66

surface mounting enclosure

ENCLOSURE

| | Description | DIN modules | Dimensions (mm) | Dissipated power (*) | Pack/Quantity | Socket outlets | Cat. No. |
|-------------------------------------------------------------------------------------|-------------|-------------|-----------------|----------------------|---------------|----------------|----------------|
|  | BLOCK1 | 4 | 110x280x95 | 8W | 1 | 1 | ⊕ 632.1500-000 |
|  | BLOCK3 | 6 | 136x440x105 | 9W | 1 | 3 | ⊕ 632.3500-000 |
|  | BLOCK4 | 11 | 212x415x105 | 14W | 1 | 4 | ⊕ 632.4500-000 |
|  | BLOCK5 | 14 | 272x414x110 | 15W | 1 | 5 | 632.5500-000 |

⊕ Pack/Quantity

(*) According to CEI 23-49 Italian standard.


■ Cut-outs suitable for 32A socket outlets with 84x106 mm flange.

(x) Does not accept COMMAND 63A Series Switches and higher.

(•) 70x87 mm cut-outs.

⊕ PANEL FLANGE
70x87

ACCESSORIES

| | Description | Flange | Pack/Quantity | Cat. No. |
|-------------------------------------------------------------------------------------|--------------------------|--------|---------------|----------|
|  | Plate for panel cut-outs | 70x87 | 25 | 654.0100 |

⊕ Pack/Quantity