

Switch - Disconnectors

Surface / Flush Mount Engg Plastic IP65

■ ROTARY ISOLATORS



General Use



Emergency Use

	Current rating	No of poles	Dimensions (mm)	□	Cat. No.	
					General Use	Emergency Use
	20A	2	136x125	1/12	590.GR2002	-
	20A	2	136x125	1/12	-	590.ER2002
	20A	4	136x125	1/12	590.GR2004	-
	20A	4	136x125	1/12	-	590.ER2004
	32A	2	136x125	1/12	590.GR3202	-
	32A	2	136x125	1/12	-	590.ER3202
	32A	4	136x125	1/12	590.GR3204	-
	32A	4	136x125	1/12	-	590.ER3204
	40A	2	136x125	1/12	590.GR4002	-
	40A	2	136x125	1/12	-	590.ER4002
	40A	4	136x125	1/12	590.GR4004	-
	40A	4	136x125	1/12	-	590.ER4004



*** Pl note that Surface mounting Box 572.0310 to be used for Surface Mounting purpose and Flush Mounting Box along with Frame (572.0200 + 572.0220) to be used for Flush Mounting purpose along with above Cat. Nos.

Switch - Disconnectors



Surface mount Engg Plastic IP65

■ ROTARY ISOLATORS

	Current rating	No of poles	Dimensions (mm)	□	Cat. No.	
					General Use	Emergency Use
	20A	2	105x150x82	1/12	590.GE2012	-
	20A	4	105x150x82	1/12	590.GE2014	-
	32A	2	105x150x82	1/12	590.GE3212	-
	32A	4	105x150x82	1/12	590.GE3214	-
	40A	2	105x150x82	1/12	590.GE4012	-
	40A	4	105x150x82	1/12	590.GE4014	-
	63A	4	210x155x107	1/5	590.GE6304	-
	80A	4	210x155x107	1/5	590.GE8004	-
	100A	4	210x155x107	1/5	590.GE10004	-
	125A	4	308x228x128	1/5	590.GE12504	-